


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:230.47V I:0.0295A P:6.1376W PF:0.9029 Freq:49.99Hz Lamp Flux:551.246x1 lm		
NAME: 5RS150	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 89.81 lm/W			
MODEL	4000K	Imax(cd)	537.2	S/MH(C0/180)	0.92
NOMINAL POWER(W)	6	LOR(%)	100.0	S/MH(C90/270)	0.85
RATED VOLTAGE(V)	230	TOTAL FLUX(lm)	551.25	h UP,DN(C0-180)	0.1,48.8
NOMINAL FLUX(lm)	551.246	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.1,50.9
LAMPS INSIDE	1	h up(%)	0.2	CIBSE SHR NOM	0.75
TEST VOLTAGE(V)	231.2	h down(%)	99.8	CIBSE SHR MAX	0.95

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2019-12-02

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.416
 Humidity:65.0%
 Test Distance:9.140m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	465.8	469.3	489.4	508.1	512.8	511.3	493.4	472.8	0- 10	48.82	48.82	8.86,8.86
20	353.3	351.7	388.7	410.6	415.1	411.9	382.8	354.5	10- 20	123.3	172.1	31.2,31.2
30	219.6	224.1	254.8	275.6	282.7	277.1	250.8	229.2	20- 30	144.6	316.6	57.4,57.4
40	108.4	107.9	130.6	156.6	164.4	158.8	132.6	113.6	30- 40	119.0	435.6	79,79
50	37.68	37.10	47.33	56.72	66.19	64.16	51.50	39.13	40- 50	66.74	502.4	91.1,91.1
60	14.99	14.55	16.93	20.30	23.11	23.51	17.82	15.31	50- 60	27.21	529.6	96.1,96.1
70	7.356	7.316	8.471	9.690	10.73	10.29	8.470	7.498	60- 70	12.68	542.2	98.4,98.4
80	2.442	2.457	3.484	4.223	4.473	4.152	3.063	2.488	70- 80	6.205	548.5	99.5,99.5
90	0	0.0001	0.0393	0.1713	0.2632	0.1733	0	0	80- 90	1.557	550.0	99.8,99.8
100	0	0	0	0	0.0064	0	0	0	90-100	0.0064	550.0	99.8,99.8
110	0	0	0.0065	0	0.0130	0.0130	0.0325	0.0390	100-110	0.0061	550.0	99.8,99.8
120	0.1167	0.0908	0.0584	0.0325	0.0584	0.0586	0.0780	0.0977	110-120	0.0326	550.1	99.8,99.8
130	0.1881	0.1946	0.1752	0.1234	0.1492	0.1558	0.1884	0.2211	120-130	0.1025	550.2	99.8,99.8
140	0.3955	0.3633	0.3232	0.2731	0.3050	0.3052	0.3509	0.3839	130-140	0.1915	550.3	99.8,99.8
150	0.5693	0.5905	0.5065	0.4811	0.4995	0.5128	0.5586	0.5983	140-150	0.2703	550.6	99.9,99.9
160	0.8043	0.7917	0.7209	0.6892	0.7266	0.7336	0.7667	0.8000	150-160	0.2965	550.9	99.9,99.9
170	0.9403	0.9280	0.9222	0.8973	0.9211	0.9152	0.9419	0.9624	160-170	0.2372	551.2	100,100
180	1.025	1.025	1.026	1.034	1.025	1.025	1.033	1.027	170-180	0.0924	551.2	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2019-12-02

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.416
 Humidity:65.0%
 Test Distance:9.140m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:230.47V I:0.0295A P:6.1376W PF:0.9029 Freq:49.99Hz Lamp Flux:551.246x1 lm		
NAME: 5RS150	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	3410	10311
80	11213	15978
75	13232	16774
70	17150	19721
65	19215	21701
60	23905	26966
55	30910	36172
50	46742	58635
45	74826	92233


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2019-12-02

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.416
Humidity:65.0%
Test Distance:9.140m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:230.47V I:0.0295A P:6.1376W PF:0.9029 Freq:49.99Hz Lamp Flux:551.246x1 lm		
NAME: 5RS150	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.09	1.06	1.04	1.07	1.04	1.02	1.03	1.01	.99	.99	.97	.96	.96	.94	.93	.91
2.0	1.00	.96	.92	.98	.94	.91	.95	.92	.89	.92	.89	.87	.89	.87	.85	.83
3.0	.92	.86	.82	.91	.85	.81	.88	.84	.80	.85	.82	.79	.83	.80	.77	.76
4.0	.85	.79	.74	.84	.78	.73	.82	.76	.72	.79	.75	.72	.77	.74	.71	.69
5.0	.79	.72	.67	.78	.72	.67	.76	.70	.66	.74	.69	.66	.72	.68	.65	.63
6.0	.73	.66	.62	.72	.66	.61	.71	.65	.61	.69	.64	.60	.68	.63	.60	.58
7.0	.68	.61	.57	.67	.61	.57	.66	.60	.56	.65	.60	.56	.64	.59	.56	.54
8.0	.64	.57	.52	.63	.57	.52	.62	.56	.52	.61	.56	.52	.60	.55	.52	.50
9.0	.60	.53	.49	.59	.53	.49	.58	.52	.48	.57	.52	.48	.56	.52	.48	.47
10.0	.56	.50	.46	.56	.50	.45	.55	.49	.45	.54	.49	.45	.53	.48	.45	.44



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2019-12-02

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.416
 Humidity: 65.0%
 Test Distance: 9.140m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:230.47V I:0.0295A P:6.1376W PF:0.9029 Freq:49.99Hz Lamp Flux:551.246x1 lm		
NAME: 5RS150	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.205	.117	.037	.199	.113	.036	.186	.107	.034	.174	.100	.032	.163	.094	.030	
2.0	.197	.108	.033	.192	.106	.033	.181	.100	.031	.171	.096	.030	.161	.091	.029	
3.0	.188	.100	.030	.183	.098	.029	.173	.094	.029	.164	.090	.028	.156	.087	.027	
4.0	.178	.092	.027	.173	.091	.027	.165	.088	.026	.158	.085	.026	.150	.082	.025	
5.0	.169	.086	.025	.165	.085	.025	.157	.082	.024	.151	.080	.024	.144	.077	.023	
6.0	.160	.080	.023	.156	.079	.023	.150	.077	.022	.144	.075	.022	.138	.073	.022	
7.0	.152	.075	.021	.149	.074	.021	.143	.072	.021	.138	.071	.021	.133	.069	.020	
8.0	.144	.071	.020	.142	.070	.020	.137	.068	.019	.132	.067	.019	.127	.065	.019	
9.0	.138	.067	.019	.135	.066	.018	.131	.065	.018	.126	.063	.018	.122	.062	.018	
10.0	.131	.063	.017	.129	.062	.017	.125	.061	.017	.121	.060	.017	.117	.059	.017	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.192	.192	.192	.164	.164	.164	.112	.112	.112	.064	.064	.064	.021	.021	.021	
1.0	.175	.159	.144	.150	.136	.124	.102	.094	.086	.059	.054	.050	.019	.017	.016	
2.0	.161	.134	.111	.138	.115	.096	.095	.080	.067	.055	.046	.039	.018	.015	.013	
3.0	.150	.115	.088	.129	.100	.076	.089	.069	.053	.051	.040	.031	.016	.013	.010	
4.0	.141	.101	.071	.121	.087	.061	.083	.061	.043	.048	.036	.026	.015	.012	.008	
5.0	.133	.090	.058	.114	.078	.051	.079	.054	.036	.046	.032	.021	.015	.010	.007	
6.0	.126	.081	.049	.108	.070	.042	.075	.049	.030	.043	.029	.018	.014	.009	.006	
7.0	.119	.074	.041	.103	.064	.036	.071	.045	.026	.041	.026	.015	.013	.009	.005	
8.0	.114	.067	.036	.098	.059	.031	.068	.041	.022	.039	.024	.013	.013	.008	.004	
9.0	.108	.062	.031	.093	.054	.027	.065	.038	.019	.038	.022	.012	.012	.007	.004	
10.0	.104	.058	.028	.089	.050	.024	.062	.035	.017	.036	.021	.010	.012	.007	.003	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2019-12-02

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.416
Humidity:65.0%
Test Distance:9.140m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:230.47V I:0.0295A P:6.1376W PF:0.9029 Freq:49.99Hz Lamp Flux:551.246x1 lm											
NAME: 5RS150						TYPE:			WEIGHT:		
SPEC.:						DIM.:			SERIAL No.:		
MFR.:						SUR.:			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	25.0	26.1	25.2	26.2	26.4	25.8	26.8	26.0	27.0	27.2	
	3H	25.1	26.1	25.4	26.3	26.5	25.9	26.9	26.2	27.1	27.3
	4H	25.2	26.1	25.4	26.3	26.6	26.0	26.9	26.3	27.1	27.4
	6H	25.2	26.0	25.5	26.3	26.6	26.0	26.9	26.3	27.2	27.4
	8H	25.1	26.0	25.5	26.3	26.5	26.0	26.9	26.3	27.1	27.4
	12H	25.1	25.9	25.4	26.2	26.5	26.0	26.8	26.3	27.1	27.4
4H	2H	24.9	25.9	25.2	26.1	26.3	25.6	26.6	25.9	26.8	27.1
	3H	25.2	26.0	25.5	26.3	26.5	25.9	26.7	26.2	27.0	27.3
	4H	25.2	26.0	25.6	26.3	26.6	26.0	26.8	26.4	27.1	27.4
	6H	25.3	26.0	25.7	26.3	26.7	26.1	26.8	26.5	27.1	27.5
	8H	25.3	25.9	25.7	26.3	26.6	26.2	26.8	26.6	27.1	27.5
	12H	25.3	25.8	25.7	26.2	26.6	26.2	26.7	26.6	27.1	27.5
8H	4H	25.2	25.8	25.6	26.2	26.6	26.0	26.6	26.4	26.9	27.3
	6H	25.3	25.8	25.8	26.2	26.6	26.1	26.6	26.6	27.0	27.5
	8H	25.3	25.8	25.8	26.2	26.6	26.2	26.6	26.6	27.1	27.5
	12H	25.3	25.7	25.8	26.1	26.6	26.2	26.6	26.7	27.0	27.5
12H	4H	25.2	25.7	25.6	26.1	26.5	25.9	26.5	26.4	26.9	27.3
	6H	25.3	25.7	25.8	26.2	26.6	26.1	26.5	26.6	27.0	27.4
	8H	25.3	25.7	25.8	26.1	26.6	26.2	26.5	26.6	27.0	27.5
Variations with the observer position at spacings:											
S = 1.0H	+ 1.6 / - 2.7					+ 1.8 / - 2.6					
1.5H	+ 2.6 / - 2.4					+ 2.9 / - 2.5					
2.0H	+ 3.5 / - 2.2					+ 3.9 / - 2.3					

CIE Pub.117, 551.2 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -2.1)
Area: 0.001256 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2019-12-02

g Range: 0 - 180DEG
g Interval: 1.0DEG
g Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.416
Humidity:65.0%
Test Distance:9.140m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:230.47V I:0.0295A P:6.1376W PF:0.9029 Freq:49.99Hz Lamp Flux:551.246x1 lm		
NAME: 5RS150	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	78	70	66	78	70	66	77	70	65	61
0.80	87	79	75	86	79	75	85	78	74	70
1.00	93	86	81	92	85	81	90	86	81	76
1.25	98	92	87	97	91	87	95	90	86	81
1.50	101	95	91	100	95	91	98	93	90	84
2.00	105	100	96	104	99	95	101	97	94	88
2.50	107	103	99	106	101	98	102	99	96	90
3.00	109	105	102	108	104	101	104	101	99	92
4.00	112	108	106	110	107	104	106	104	101	94
5.00	113	110	108	111	109	106	107	105	103	95
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2019-12-02

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.416
Humidity:65.0%
Test Distance:9.140m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:230.47V I:0.0295A P:6.1376W PF:0.9029 Freq:49.99Hz Lamp Flux:551.246x1 lm		
NAME: 5RS150	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2019-12-02

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.416
Humidity:65.0%
Test Distance:9.140m [K=1.0000]
Remarks:

AAI Figure

Test:U:230.47V I:0.0295A P:6.1376W PF:0.9029 Freq:49.99Hz Lamp Flux:551.246x1 lm		
NAME: 5RS150	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:

Flux out:302.7 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2019-12-02

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.416
 Humidity: 65.0%
 Test Distance: 9.140m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

Test:U:230.47V I:0.0295A P:6.1376W PF:0.9029 Freq:49.99Hz Lamp Flux:551.246x1 lm		
NAME: 5RS150	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2019-12-02

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.416
Humidity: 65.0%
Test Distance: 9.140m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:230.47V I:0.0295A P:6.1376W PF:0.9029 Freq:49.99Hz Lamp Flux:551.246x1 lm		
NAME: 5RS150	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	24553
L_0~180(75)av	18612
L_0~180(85)av	12893
L_90~270(65)av	22845
L_90~270(75)av	16670
L_90~270(85)av	10572
L_45(65)av	23593
L_45(75)av	18117
L_45(85)av	11671

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2019-12-02

g Range: 0 - 180DEG
g Interval: 1.0DEG
g Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.416
Humidity:65.0%
Test Distance:9.140m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2019-12-02

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.416
Humidity: 65.0%
Test Distance: 9.140m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:230.47V I:0.0295A P:6.1376W PF:0.9029 Freq:49.99Hz Lamp Flux:551.246x1 lm		
NAME: 5RS150	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:

Table--1

UNIT: cd

C(°) g (°)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	532	532	532	532	532	532	532	532	532	532	532	532	532	532	532	532			
5	508	507	509	514	519	527	532	535	536	535	534	530	524	517	514	509			
10	466	468	469	480	489	502	508	513	513	512	511	503	493	482	473	467			
15	417	412	414	432	445	459	462	468	467	464	469	457	446	433	421	413			
20	353	348	352	372	389	405	411	415	415	408	412	398	383	372	354	349			
25	283	281	285	301	319	333	347	348	352	348	342	329	311	299	287	284			
30	220	218	224	237	255	269	276	280	283	281	277	262	251	237	229	221			
35	161	159	162	175	191	209	217	222	224	224	217	203	193	175	170	161			
40	108	106	108	119	131	149	157	163	164	164	159	143	133	120	114	108			
45	66.4	63.4	63.1	71.5	81.9	93.5	99.9	106	108	110	106	93.6	86.3	75.8	68.7	65.5			
50	37.7	36.6	37.1	40.2	47.3	52.5	56.7	62.8	66.2	66.7	64.2	55.6	51.5	43.1	39.1	38.2			
55	22.2	21.5	21.4	24.1	26.1	30.0	32.6	37.0	38.1	39.0	37.8	32.4	29.4	25.1	23.7	22.1			
60	15.0	14.4	14.6	15.9	16.9	18.9	20.3	21.6	23.1	24.1	23.5	19.4	17.8	16.0	15.3	14.7			
65	10.2	9.76	9.88	10.7	11.5	13.4	14.2	15.1	15.9	15.7	15.3	13.4	12.7	11.8	10.8	10.2			
70	7.36	7.19	7.32	7.85	8.47	9.13	9.69	10.4	10.7	10.5	10.3	8.99	8.47	7.95	7.50	7.39			
75	4.30	4.21	4.38	4.83	5.45	6.52	7.23	7.63	7.81	7.75	7.42	6.25	5.39	4.68	4.54	4.36			
80	2.44	2.34	2.46	2.97	3.48	3.96	4.22	4.41	4.47	4.41	4.15	3.58	3.06	2.63	2.49	2.43			
85	0.37	0.28	0.33	0.57	1.13	1.79	2.23	2.50	2.45	2.34	2.01	1.55	1.19	0.65	0.53	0.43			
90	0.00	0.00	0.00	0.00	0.04	0.01	0.17	0.22	0.26	0.33	0.17	0.01	0.00	0.00	0.00	0.00			
95	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
100	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
105	0.00	0.03	0.00	0.01	0.01	0.01	0.00	0.01	0.01	0.00	0.01	0.00	0.01	0.00	0.02	0.00			
110	0.00	0.04	0.00	0.04	0.01	0.02	0.00	0.01	0.01	0.00	0.01	0.00	0.03	0.00	0.04	0.00			
115	0.04	0.07	0.01	0.06	0.01	0.05	0.00	0.04	0.04	0.00	0.03	0.00	0.04	0.01	0.05	0.02			
120	0.12	0.11	0.09	0.10	0.06	0.07	0.03	0.07	0.06	0.02	0.06	0.02	0.08	0.08	0.10	0.08			
125	0.12	0.16	0.10	0.15	0.08	0.12	0.08	0.10	0.10	0.08	0.11	0.07	0.12	0.10	0.15	0.11			
130	0.19	0.23	0.19	0.20	0.18	0.17	0.12	0.16	0.15	0.11	0.16	0.13	0.19	0.18	0.22	0.19			
135	0.28	0.31	0.29	0.28	0.22	0.25	0.19	0.23	0.23	0.18	0.23	0.19	0.26	0.25	0.30	0.30			
140	0.40	0.42	0.36	0.37	0.32	0.33	0.27	0.31	0.31	0.27	0.31	0.28	0.35	0.33	0.38	0.38			
145	0.48	0.51	0.46	0.49	0.40	0.44	0.39	0.41	0.40	0.38	0.40	0.40	0.45	0.43	0.49	0.48			
150	0.57	0.62	0.59	0.59	0.51	0.54	0.48	0.50	0.50	0.46	0.51	0.49	0.56	0.53	0.60	0.56			
155	0.70	0.73	0.71	0.69	0.62	0.64	0.59	0.63	0.62	0.57	0.62	0.60	0.66	0.64	0.71	0.68			
160	0.80	0.83	0.79	0.79	0.72	0.75	0.69	0.74	0.73	0.69	0.73	0.71	0.77	0.75	0.80	0.78			
165	0.88	0.91	0.86	0.88	0.82	0.85	0.81	0.84	0.83	0.80	0.83	0.81	0.86	0.83	0.90	0.89			
170	0.94	0.97	0.93	0.96	0.92	0.94	0.90	0.92	0.92	0.89	0.92	0.90	0.94	0.93	0.96	0.94			
175	1.01	1.02	1.00	1.01	0.98	0.99	0.95	0.99	0.99	0.95	0.99	0.95	1.00	0.98	1.01	1.00			
180	1.02	1.02	1.03	1.03	1.03	1.02	1.03	1.02	1.02	1.02	1.03	1.03	1.03	1.02	1.03	1.04			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2019-12-02

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.416
Humidity:65.0%
Test Distance:9.140m [K=1.0000]
Remarks: